

DT90A1008



Digital non-programmable thermostat with large LCD display and simple user interface.

Product Description

Digital non-programmable thermostat with large LCD display and simple user interface. For general purpose control of boilers, zone valves, pumps, thermal actuators, electric heaters and fan-coil units.

- self-learning TPI Fuzzy logic control
- adjustable proportional band
- adjustable on/off time
- frost protection
- setpoint limits
- fail-safe operation
- installer mode

Technical Properties

Heat/Cool manual mode	H/C
Approvals	CE
ErP Class	IV
Manual operation functions	-off/standby, -setpoint, -ECO

Temp. setpoint range	5 ... 35 °C
Control output signal	on/off
Switch function/capacity	SPDT 24..230 Vac, 8 A resistive, 3 A inductive; potential free
Earthing	double insulated
Housing (HxWxD)	92 mm 90 mm 27 mm
Protection class	IP30
Terminal max. wire size	2.5 mm ²
Battery life	minimum 2 years
Power source	battery powered, 2 x 1,5 V AA Alkaline cells
Product literature language	multilanguage user guide included in package
Model	standard

Related Material



d1069-06-doc-uk07r
Multilingual
DECLARATION OF CONFORMITY



dt90uk07bwhres.tif

tif



dt90uk07cohres.tif

tif



dt90uk07colres.jpg

jpg